

## KONICA MINOLTA Bizhub 25e

Viteza A4: alb-negru 25 ppm  
Formate hartie: A6-A4 si formate personalizate  
Capacitate de pana la 2.100 coli in pana la 5 tavi  
Alimentator automat de documente reverse  
Panou de comanda monocrom, tactil de 5.7 inch



Imaginea este cu titlu de prezentare

### Sisteme de operare



### Specificatii copiator

Proces copiere	Copiere LED electrostatic, mono component
Sistem toner	Toner polimerizat
Viteza copiere/printare A4 alb negru	Pana la 25 cpm
Viteza duplex A4 alb negru	Pana la 10 cpm
Prima pagina copiata/printata alb negru	5 sec.
Timpul de incalzire (sec)	Aprox. 12 sec.
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1-99
Format documente originale	Max. A4
Marire-micsorare	25-400 % in pasi de 1%
Functii copiere	Copiere duplex, sortare electronica, rotire copie, 2in1, 4in1, copiere act de identitate, setari dimensiuni particularizate

### Specificatii imprimanta

Rezolutie printare	600 x 600 dpi
Procesor	366 MHz
Limbaje printare	GDI PCL 5e/XL PostScript 3 (optional) Printare directa PDF (optional) Printare coduri de bare si fonturi OCR (optional)
Sisteme operare	Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003/2008 (32/64) 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix SAP AS/400

### Fonturi printare

80 PCL Latin  
136 PostScript 3 Emulation Latin (optional)  
32 Barcode/OCR (optional)  
Printare duplex, inserare coperta, sortare electronica, ajustare densitate, mod economisire toner, n-up, watermark (doar PCL, PostScript 3), printare securizata

### Functii printare

### Specificatii scanner

Viteza scanare color Pana la 27 opm  
Viteza scanare alb negru (opm) Pana la 40 opm  
Rezolutie scanare Max.: 600 x 600 dpi  
Moduri scanare Scan-to-eMail  
Scan-to-SMB  
Scan-to-FTP  
Scan-to-USB  
TWAIN local/retea  
Formate fisier PDF, PDF criptat, TIFF, JPEG  
Destinatii scanare 1,030 (simplu + grup); suport LDAP

### Specificatii fax

Standard fax Super G3  
Transmisie fax Analog; PC-Fax; i-Fax  
Rezolutie fax Max.: 406 x 392 dpi  
Compresie fax MH; MR; MMR; JBIG  
Modem fax 33.6 Kbps  
Destinatii fax 1030  
Functii fax Transmisie intarzziata, fax forwarding automat

### Specificatii sistem

Memorie sistem standard 512 MB + 128 MB SD card  
Interfete standard 10-Base-T/100-Base-TX; USB 2.0  
TCP/IP (IPv4, IPv6); IPP, SNMP, HTTP, HTTPS  
Protocoale de retea Ethernet II  
Tipuri frame-uri Ethernet II  
Alimentator automat documente Pana la 80 originale; A5-A4; 35-128 g/m<sup>2</sup>  
Alimentator automat de documente duplex

Format hartie	A6-A4, dimensiuni hartie particularizate (90-216 x 140-356 mm)	Durata viata toner Black	Pana la 20,000 pagini
Greutate hartie	60-160 g/m <sup>2</sup>	Consum energie	220-240 V / 50/60 Hz
Capacitate alimentare hartie (coli)	Standard: 600; Max.: 2,100		Mai putin de 1.09 kW (sistem)
Casete hartie standard	Caseta 1: 500 coli, A5-A4, 60-90 g/m <sup>2</sup>	Dimensiuni sistem (LxIxH)	520 x 513 x 509
	Alimentare manuala (bypass): 100 coli, A6-A4, dimensiuni hartie particularizate (90-216 x 140-356 mm), 60-160 g/m <sup>2</sup>	Greutate sistem	Aprox. 24.1 kg
	Casetele 3 + 4: 500 coli fiecare, A5-A4, 60-90 g/m <sup>2</sup>	<b>Funcții sistem</b>	Blocare adresa Mac; blocare adresa IP; SSL; HTTPS; PDF criptat; autentificare utilizator; printare securizata
Casete hartie optional Duplex automat	A6-A4; 60-90 g/m <sup>2</sup>	Securitate	
Capacitate iesire (cu finisher)	Std.: 250 coli		Pana la 100 conturi de utilizator; suport Active Directory 2003; definire acces la functiile echipamentului
	Max.: 350 coli (induzand separatorul de joburi extern optional)	Contorizare	
Volum copiere/printare maxim (lunar)	Rec.: 5,000 pagini; Max.: 10,000 pagini	Software	PageScope Net Care Device Manager