

KONICA MINOLTA Bizhub 362

Functii:
Copiere - standard
Imprimare - standard
Scanare - standard

Format A3
Tehnologie Laser
Mod tiparire Monocrom
Interfata USB, Retea

SPECIFICATII COPIATOR

Proces copiere	Laser electrostatic, Tandem, Indirect
Sistem toner	Toner polimerizat Simitri HD™
Viteza copiere/printare A4 alb negru	Pana la 36 cpm
Viteza copiere/printare A3 alb negru	Pana la 16 cpm
Viteza duplex A4 alb negru	Pana la 36 cpm
Prima pagina copiata/printata alb negru	4,2sec
Timpul de incalzire	Aprox. 25sec
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1 - 9,999
Format documente originale	A5-A3
Marire-micsorare	25 - 400% in pasi de 0.1%
Functii copiere	Capitol, inserare pagina si coperta Copie de test (printare, pe ecran cu HDD) Printare test pentru ajustare Functii pentru arta digitala Memorare setari joburi Mod poster, Repetare imagini Overlay, Watermark, Stampilare, Protejare la copiere Card Shot

SPECIFICATII IMPRIMANTA

Rezolutie printare	Echivalent cu 1800 x 600 dpi
Procesor	667 MHz PCL6, PCL5e/c (XL3.0), PostScript 3 (CPSI 3016), XPS
Limbaje printare	Window s 2000 / XPx32 / XPx64 Window s VISTA x32 / x64 Window s 7 x32 / x64
Sisteme operare	Suport Window s DPWS Macintosh 9.2 / 10.2 / 10.4 Server 2000 / 2003 / 2003x64 / 2008 / 2008x64 Unix/Linux/Citrix
Fonturi printare	80x PCL Latin, 137x PostScript 3 Emulation Latin
Functii printare	Printare directa fisiere PCL, PS, TIFF, JPEG, XPS, PDF si PDF criptate Mixmedia si Mixplex Programare joburi "Easy Set" Overlay, Watermark, Protejare la copiere



Imaginea este cu titlu de prezentare

SPECIFICATII SCANNER

Viteza scanare alb negru	Color/Alb negru pana la 70 opm (300 dpi prin DF) Color/Alb negru pana la 42 opm (600 dpi prin DF)
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scanare Retea TWAIN Scan-to-eMail (Scan-to-Me) Scan-to-FTP Scan-to-SMB (Scan-to-Home) Scan-to-Box (necesita HDD) Scan-to-WebDAV Scan-to-DPWS Scan-to-USB JPEG; TIFF; PDF; PDF compact; PDF criptat; Outline PDF; Searchable PDF (optional); XPS; XPS compact Adnotare (text/ora/data) pentru PDF (necesita HDD) Pana la 400 programe joburi
Formate fisier	
Functii scanare	

SPECIFICATII FAX

Standard fax	Suoer G3 (optional)
Transmisie fax	Analog, IP-Fax
Rezolutie fax	Max.: 600 x 600 dpi (ultra fin)
Compresie fax	MH, MR, MMR, JBIG
Modem fax	2100 (simplu+grup)
Functii fax	Polling Transmisie intarziata PC-Fax Receptionare confidentiala in box (necesita HDD) Receptie pe email, FTP, SMB Pana la 400 programe joburi

SPECIFICATII SISTEM

Memorie sistem standard	2048 MB	Casete hartie standard	Caseta 3: 500 coli, A5 - A3, 60 - 90 g/m ² Casetele 3 + 4: 2x 500 coli, A5 - A3, 60 - 90 g/m ² Caseta de mare capacitate: 2,500 coli, A4, 60 - 90 g/m ² A5 - A3, 60 - 90 g/m ²
Hard disk sistem optional	250 GB	Duplex automat	
Interfete standard	10Base-T/100Base-T/1000Base-T Ethernet, USB 2.0	Volum copiere/printare recomandat (lunar)	4800
Alimentator automat documente	Pana la 100 originale A6-A3 35-128 g/m ² simplex 50-128 g/m ² duplex A6-A3, Dimensiuni hartie particularizate (90-297 x 139.7-431.8 mm)	Volum copiere/printare maxim (lunar)	28000
Format hartie		Consum energie	220-240 V / 50/60Hz, mai putin de 1.5 KW
Greutate hartie	60-210 g/m ²	Dimensiuni sistem (Lxlxh)	623 x 794 x 700
Capacitate alimentare hartie	Standard:1,150 coli, Max.: 3,650 coli	Greutate sistem	Aprox. 66kg