

KONICA MINOLTA Bizhub 364e

Viteza A4/A3: 36/18 ppm alb-negru
Formate hartie: A6-SRA3, formate customizate si format banner de pana la 1,2 metri lungime
Panou tactil, color, de 9 inch cu functionalitati multi-touch
Alimentatorul dual de documente - optional - scaneaza ambele fete ale originalelor dubla fata la o singura trecere la viteza de 160 ipm
Finisare modulara si optiuni ale tavilor de alimentare pentru configuratii customizate



Sisteme de operare



Specificatii copiator

Proces copiere	Copiere electrostatica laser
Sistem toner	Simitri™ - toner polimerizat
Viteza copiere/printare A4 alb negru	Pana la 36 ppm
Viteza copiere/printare A3 alb negru	Pana la 18 ppm
Viteza duplex A4 alb negru	Pana la 36 ppm
Prima pagina copiată/printată alb negru	5.3 sec
Timpul de incalzire	Aprox. 20 sec ¹ Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1 - 9,999
Format documente originale	A5 - A3 25-400% in pasi de 0.1%; zoom automat
Marire-micsorare	Capitol; inserare pagina si capitol; copie de test (print si ecran); ajustare test de print; functii arta digitala; memorare setari joburi; mod poster; repetare imagine; overlay (optional); stampilare; protejare la copiere
Functii copiere	

Specificatii imprimanta

Rezolutie printare	1,800 x 600 dpi; 1,200 x 1,200 dpi PCL6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS
Limbaje printare	

Sisteme operare

Windows XP (32/64)
Windows VISTA (32/64)
Windows 7 (32/64)
Windows 8 (32/64)
Windows Server 2003 (32/64)
Windows Server 2008 (32/64)
Windows Server 2008 R2 (64)
Windows Server 2012 (64)
Macintosh OS X 10.x
Unix, Linux, Citrix
80 PCL Latin; 137 PostScript 3
Emulation Latin

Fonturi printare

Printare directa PCL, PS, TIFF, XPS, PDF, fisiere PDF criptate si OOXML (DOCX, XLSX, PPTX); mixmedia si mixplex; programare joburi "Easy Set"; overlay; watermark; protejare copiere; carbon copy print

Functii printare

Specificatii scanner

Viteza scanare alb negru	Pana la 160 ipm
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-Web DAV Scan-to-DPWS Scanare TWAIN in retea JPEG; TIFF; PDF; PDF/A 1a si 1b (optional); PDF compact; PDF criptat; PDF indexabil (optional); XPS; XPS compact; PPTX; PPTX indexabil (optional); DOCX/XLSX indexabil (optional)
Formate fisier	

Imaginea este cu titlu de prezentare

Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP	Duplex automat	A5-SRA3; 52-256 g/m ²
Functii scanare	Adnotare (text/timp/data) pentru PDF; pana la 400 programe joburi; previzualizare scanare in timp real	Moduri finisare (optional)	Offset; grupare; sortare; capsare; perforare; post inserare; pliere mediana; pliere in forma de scrisoare; brosurare
Specificatii fax		Capacitate iesire (cu finisher)	Max.: 3,300 coli
Standard fax	Super G3 (optional)	Capacitate iesire (fara finisher)	Max.: 250 coli
Transmisie fax	Analog i-Fax i-Fax color (RFC3949-C) IP-Fax	Capsare	Max.: 50 coli sau 48 coli + 2 coperti (pana la 209 g/m ²)
Rezolutie fax	Max.: 600 x 600 dpi (ultra-fine)	Capacitate iesire la capsare	Max.: 1,000 coli
Compresie fax	MH; MR; MMR; JBIG	Pliere in forma de scrisoare	Pana la 3 coli
Modem fax	Pana la 33.6 Kbps	Capacitate coli pliate in forma de scrisoare	Max.: 30 coli (tava); nelimitat Max.: 20 coli sau 19 coli + 1 coperta (pana la 209 g/m ²)
Destinatii fax	2,100 (utilizatori + grupuri)	Brosura	Max.: 100 coli (tava); nelimitat
Functii fax	Polling; transmisie intarzziata; PC-Fax; receptie confidentiala in box; Receptie pe e-mail/FTP/SMB; pana la 400 programe joburi	Capacitate iesire brosurii	
Specificatii user box		Volum copiere/printare recomandat (lunar)	25000
Nr. maxim documente care se pot stoca	Pana la 3,000 documente sau 10,000 pagini	Volum copiere/printare maxim (lunar)	48000
Tipuri de user box	Public	Durata viata toner Black	28800
		Durata viata unitate imagine Black	120,000 pagini/600,000 pagini (Drum/Developer)
Tipuri de boxuri sistem	Personal (cu parola sau autentificare) Grupuri cu autentificare	Consum energie	220-240 V / 50/60 Hz; Mai putin de 1.58 kW (sistem)
	Printare securizata Printare PDF criptat Receptie fax Fax polling	Dimensiuni sistem (Lxhxh)	615 x 685 x 779 mm (fara ADF si casete suplimentare)
Functionalitati user box	Reprintare; combinare Descarcare Trimitere (e-mail/FTP/SMB si fax) Copiere din box in box	Greutate sistem	Aprox. 76.5 kg
Specificatii sistem		Functii sistem	
Memorie sistem standard	2048 MB	Securitate	ISO 15408 EAL3 (in evaluare); conform IEEE 2600.1; filtrare IP si blocare porturi; criptare comunicare in retea SSL2; SSL3 si TLS1.0; suport IPsec; suport IEEE 802.1x; autentificare utilizatori;
Hard disk sistem standard	250 GB		raport autentificare; printare securizata; suprascriere hard disk (8 tipuri standard);
Interfete standard	10-Base-T/100-Base-T/1,000-Base-T Ethernet, USB 2.0		criptare date pe hard disk (AES 128); stergere automata a datelor din memorie; receptionare confidentiala a faxurilor;
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP		Criptarea datelor de printare; protectie la copiere (Copy Guard, Password Copy) optional
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP		
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-163 g/m ² RADF sau ADF dualscan		
Format hartie	A6-SRA3, formate hartie particularizate; hartie banner max. 1,200 x 297 mm		
Greutate hartie	52-300 g/m ²		
Capacitate alimentare hartie	Standard: 1150 coli Max.: 3650 coli	Contorizare	Pana la 1,000 conturi utilizatori; suport Active Directory (nume utilizator + parola + e-mail + folder smb) Definire acces utilizatori
Casete hartie standard	Caseta 1: 500 coli, A5-A3, 52-256 g/m ² Caseta 2: 500 coli, A5-SRA3, 52-256 g/m ² Alimentare manuala (bypass): 150 coli, A6-SRA3, dimensiuni particularizate, banner, 60-300 g/m ²		Autentificare biometrica (scanarea dispunerii venelor in sange) optional Autentificare prin card IC-Card (cititor IC-Card) optional
Specificatii hartie optional	Caseta 3: 500 coli, A5-A3, 52-256 g/m ² Casetele 3 + 4: 2 x 500 coli, A5-A3, 52-256 g/m ² Caseta de mare capacitate: 2,500 coli, A4, 52-256 g/m ²	Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility