

## KONICA MINOLTA Bizhub C220/C280

- Inovatie alb-negru si culoare la superlativ la viteza de 22 pagini/minut.
- Tehnologie de ultima ora pentru performante de top: 2,048 MB DDR2 RAM, 250 GB SATA-2 hard disc, 1GB Ethernet, PCI-Express bus system
- Posibilitati atractive de finisare ce includ: finisher de capsare integrat, finisher modular cu functie optionala de brosurare
- Certificat Eco-performance Energy Star si German Blue Angel: consum redus de energie si prietenos fata de mediu
- **I-Fax** optional

Volumul de lucru lunar pentru care este recomandat echipamentul este de:

volum mediu lunar: 25.000 pag. A4 (6% acoperire, 80g/m2)

volum maxim lunar: 35.000 pag. A4 (6% acoperire, 80g/m2)



Imaginea este cu titlu de prezentare

### SPECIFICATII COPIATOR

Proces copiere	Copiere laser electrostatica, tandem, indirect
Sistem toner	Toner polimerizat Simitri HD
Viteza copiere/printare A4 alb negru	22 cpm
Viteza copiere/printare A4 color	22 cpm
Viteza copiere/printare A3 alb negru	12 cpm
Viteza copiere/printare A3 color	12 cpm
Viteza duplex A4 alb negru	22 cpm
Viteza duplex A4 color	22 cpm
Prima pagina copiata/printata alb negru	7,5 s
Prima pagina copiata/printata color	11 s
Timpul de incalzire	Aprox. 45 s *
	* Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600x600 dpi
Gradatii	256
Format documente originale	A5-A3
Marire-micsorare	25-400% in pasi de 0,1%, marire-micsorare automata
Functii copiere	Capitol; Inserare capitol si coperta; Copie de test; Ajustarea printarii; Functie arta digitala Memorare setari joburi; Mod poster; Repetare imagini; Overlay; Stampilare; Protejare la copiere

### Specificatii imprimanta

Rezolutie printare	Echivalent cu 1.800 x 600 dpi
Tip procesor	MPC8533 @ 667 MHz
Limbaje printare	PCL 6c (PCL 5c + XL3.0); PostScript 3 (CPSI 3017)
Sisteme operare	Windows 2000/XP/XP64 Windows VISTA 32/64 suport DPWS Server 2000/2003/2003x64/2008/2008x64 Macintosh 9.x/10.x Unix/Linux/Citrix
Fonturi printare	80x PCL Latin; 137x PostScript 3 Emulation Latin
Functii printare	Printare directa fisiere PCL; PS; TIFF; XPS; PDF si fisiere PDF criptate; Mixmedia si mixplex; Programare joburi "Easy Set"; Overlay; Watermark; Protejare copiere
<b>Specificatii scanner</b>	
Viteza scanare color	Pana la 70 (300 dpi via DF)
Viteza scanare alb negru	Pana la 70 opm (300 dpi via DF)
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Network TWAIN scan; scan-to-eMail (scan-to-Me); scan-to-FTP; Scan-to-SMB (scan-to-Home); scan-to-Box; scan-to-WebDAV; scan-to-DPWS; scan-to-USB
Formate fisier	JPEG; TIFF; PDF; Compact PDF; PDF criptat; XPS; XPS compact
Destinatii scanare	2.100 (simple + grup); suport LDAP
Functii scanare	Adnotare (text/timp/data) pentru PDF; pana la 400 programe joburi

## Specificatii fax

Standard fax	Super G3 (optional) Analog; i-Fax; i-Fax Color (RFC3949-C); IP-Fax; SIP-Fax
Transmisie fax	Max.: 600 x 600 dpi (ultra-fin)
Rezolutie fax	MH; MR; MMR; JBIG
Compresie fax	Pana la 33,6 Kbps
Modem fax	2.100 (simplu + grup)
Destinatii fax	

Polling; Transmisie intarziata; PC-Fax; Receptie confidentiala in box; Receptie pe eMail/FTP/SMB; Pana la 400 programe joburi

## Functii fax

### Specificatii user box

Nr. maxim documente care se pot stoca	Pana la 3.000 documente sau 10.000 pagini
Tipuri de user box	Public, personal (cu autentificare prin parola), grup (cu autentificare)
Tipuri de boxuri sistem	Printare securizata, PDF criptat, Receptie fax, Fax polling
Functionalitati user box	Reprintare, combinare, download, trimitere (eMail, FTP, SMB si fax), copiere din box in box

### Specificatii sistem

Memorie sistem standard	2048 MB
Hard disk sistem standard	250 GB
Interfete standard	10-Base-T/100-Base-T/1.000-Base-T Ethernet; USB 2.0
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-210 g/m <sup>2</sup>
Format hartie	A6-A3 full bleed; formate particularizate; baner 1.200 x 297 mm
Greutate hartie	64 - 271 g/mp
Capacitate alimentare hartie	Standard: 1.150 coli Max: 3.650
Casete hartie standard	<b>Caseta 1:</b> 500 coli, A5-A3, 64-256 g/mp <b>Caseta 2:</b> 500 coli, A5-A3+, 64-256 g/mp <b>Alimentare manuala (bypass):</b> 150 coli, A6-A3+, formate particularizate, 64-271 g/mp

Duplex automat	A5-A3+; 64-256 g/mp Offset; grupare; sortare; capsare; perforare; pliere mediana; pliere in forma de scrisoare; brosură
Moduri finisare (optional)	
Capacitate iesire (cu finisher)	Max.: 3.200 coli
Capacitate iesire (fara finisher)	Max.: 250 coli
Capsare	50 coli sau 48 coli + 2 coala coperta (pana la 209 g/mp)
Capacitate capsare	Max. 1.000 coli
Brosura	15 coli sau 14 coli + 1 coala coperta (pana la 209 g/m <sup>2</sup> )

Capacitate iesire brosură	75 coli
Volum copiere/printare recomandat (lunar)	25.000 pagini
Volum copiere/printare maxim (lunar)	35.000 pagini
Consum energie	Mai putin de 1,5 KW (sistemul)

Dimensiuni sistem (Lxlxh)	643 x 842 x 770
Greutate sistem	Aprox. 98 kg

### Functii sistem

Securitate	ISO15408 EAL3 (in evaluare), filtrare IP si blocare porturi, criptare comunicare in retea SSL2, SSL3 si TSL1.0, suport IPsec, autentificare utilizatori, raport autentificare, printare securizata, suprascriere hard disk (8 tipuri standard), criptare date pe hard disk (optional), stergere automata a datelor din memorie, receptionare confidentiala a faxurilor, Copy Guard, Password copy
Contorizare	Pana la 1.000 conturi utilizatori, suport Active Directory (nume utilizator + parola + email + smb folder) Definire acces utilizatori Autentificare biometric (scanarea dispunerii venelor in deget) optional Autentificare prin card IC-Card (cititor IC-Card ) optional
Software	PageScope Net Care Device Manager; PageScope Data Administrator; PageScope Box Operator; PageScope Workware (Versiune de incercare); PageScope Direct Print; Print Status Notifier; Driver Packaging Utility; Log Management Utility