

KONICA MINOLTA Bizhub C25

Viteza A4: color 24 ppm; alb-negru 24 ppm
Formate hartie: A6-A4 si formate personalizate
Multifunctional color si alb-negru versatil cu
functii de printare, copiere si scanare
Mic, compact si usor
Mood duplex standard cu productivitate 100%



Imaginea este cu titlu de prezentare

Sisteme de operare



Specificatii copiator

Proces copiere	Copiere laser electrostatic, Tandem, indirect
Sistem toner	Simitri HD™- toner polimerizat
Viteza copiere/printare A4 alb negru	Pana la 24 cpm
Viteza copiere/printare A4 color	Pana la 24 cpm
Viteza duplex A4 alb negru	Pana la 24 cpm
Viteza duplex A4 color	Pana la 24 cpm

Prima pagina copiată/printată alb negru	11 sec.
Prima pagina copiată/printată color	16 sec.
Timpul de incalzire	Aprox. 38 sec
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1-99
Format documente originale	Max. A4
Marire-micsorare	25 - 400% in pasi de 0.1% Copiere duplex, 2in1, 4in1, ajustare densitate, copiere card ID, colationare electronica (1)
Funcții copiere	

Specificatii imprimanta

Rezolutie printare	600 x 600 dpi x 3 bit
Procesor	800 MHz
Limbaje printare	PostScript 3 (CPSI 3016), PCL6 (XL 3.0), PCL5e/c, XPS (2), PDF 1.7 Direct Printing (1)
Sisteme operare	Windows XP (32/64), Vista (32/64), 7 (32/64) Windows Server 2003 (32/64), Server 2008 (32/64) Suport Windows DPWS Macintosh OSX (10.2.8/10.3.9/10.4/10.5/10.6) Linux: SUSE, Red Hat Citrix Netware 4/5/6

Fonturi printare	80x PCL Latin, 137x PostScript 3 Emulation Latin
Funcții printare	Printare directa (1) PDF (versiunea 1.7), JPEG, TIFF, XPS (2) Overlay, watermark, n-up, poster, brosură, colationare (1)
Specificatii scanner	
Viteza scanare color	Pana la 10/20 opm (300 dpi prin DF)
Viteza scanare alb negru	Pana la 10/20 opm (300 dpi prin DF)
Rezolutie scanare	Max.: 600 x 600 dpi (doar TWAIN/WIA) Scanare TWAIN in retea, WIA Scan, Scan-to-eMail, Scan-to-FTP, Scan-to-SMB, Scan-to-USB
Moduri scanare	JPEG, TIFF, PDF
Formate fisier	Pana la 220 (partajat cu fax-ul)
Destinatii scanare	
Specificatii fax	
Standard fax	Super G3
Transmisie fax	Analog, PC-Fax
Rezolutie fax	Max.: 203 x 392 dpi (super fine)
Compresie fax	MH, MR, MMR, JBIG
Modem fax	Pana la 33,6 Kbps
Destinatii fax	Pana la 220 (partajat cu scanarea) Transmisie intarzita, Fax Forwarding catre email
Funcții fax	
Specificatii sistem	
Memorie sistem standard	256 MB, Max: 768 MB
Hard disk sistem standard	40 GB optional
Interfete standard	10Base-T/100Base-TX/1000Base-T Ethernet, USB 2.0
Protocoale de retea	TCP/IP (IPv4 / IPv6), IPX/SPX, NetBEUI AppleTalk (EtherTalk) SMB, LPD, IPP, SNMP, HTTP, HTTPS

Tipuri frame-uri	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP	■	Durata viata toner Black	preinstalat: pana la 2,000 pagini
Alimentator automat documente	Pana la 35 originale, A4, 50-110g/m ²	■	Durata viata toner CMY	inlocuire: pana la 6,000 pagini
Format hartie	A6 - A4, Dimensiuni hartie particularizate	■	Durata viata unitate imagine Black	preinstalat: pana la 2,000 pagini
Greutate hartie	60-210 g/m ²	■	Durata viata unitate imagine CMY	inlocuire: pana la 6,000 pagini
Capacitate alimentare hartie	Standard: 350 coli, Max.: 850 coli	■	Consum energie	pana la 30000 pagini
Casete hartie standard	Caseta 1: 250 coli, A6 - A4, 60 - 210 g/m ² , dimensiuni particularizate (92 - 216 x 148 - 297 mm)	■	Dimensiuni sistem (Lxhx)	220-240 V / 50/60Hz, mai putin de 1.1 KW
	Alimentare manuala (bypass): 100 coli, A6 - A4, 60 - 210 g/m ² , dimensiuni particularizate (92 - 216 x 148 - 356 mm)	■	Greutate sistem	447 x 558 x 490
Duplex automat	A4, 60 - 210 g/m ²	■	Functii sistem	Aprox. 32,5 kg
Capacitate iesire (fara finisher)	Max. 150 coli cu fata in jos	■	Securitate	filtrare IP si blocare port comunicare retea SSL2, SSL3 si TSL1.0
Volum copiere/printare recomandat (lunar)	1260 pagini	■		suport IPsec
Volum copiere/printare maxim (lunar)	120000 pagini	■	Software	suport IEEE 802.1x
		■		printare securizata (2)
		■		criptare date pe hard disc (2)
		■		PageScope Net Care Device Manger
		■		PageScope Direct Print
		■		PageScope WebConnection

