

KONICA MINOLTA Bizhub C284e

Viteza A4/A3: 28/14 ppm color si alb-negru
Formate hartie: A6-SRA3, formate customizate si format banner de pana ala 1,2 m lungime
Panou de operare tactil, color de 9 inch cu functionalitate multi-touch
Alimentator de documente cu scanare duala pentru scanarea documelor fata-verso intr-o singura trecere la viteza de 160 ipm
Finisare modulara si diverse tavi de alimentare pentru configuratii customizate

Sisteme de operare



Specificatii copiator

Proces copiere	Copiere electrostatica laser tandem indirecta
Sistem toner	Toner polimerizat Si mitri HD®
Viteza copiere/printare A4 alb negru	28 cpm
Viteza copiere/printare A4 color	28 cpm
Viteza copiere/printare A3 alb negru	14 cpm
Viteza copiere/printare A3 color	14 cpm
Viteza duplex A4 alb negru	28 cpm
Viteza duplex A4 color	28 cpm
Prima pagina copiata/printata alb negru	5.9 sec
Prima pagina copiata/printata color	7.7 sec
Timpul de incalzire	Aprox. 20 sec * Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1-9,999
Format documente originale	A5-A3
Marire-micsorare	25-400% in pasi de 0.1%; zoom automat
Functii copiere	Capitol; inserare pagina si capitol; copie de test (print si ecran); ajustare test de print; functii arta digitala; memorare setari joburi; mod poster; repetare imagine; overlay (optional); stampilare; protejare la copiere

Specificatii imprimanta

Rezolutie printare	1,800 x 600 dpi 1,200 x 1,200 dpi
Procesor	800 MHz
Limbaje printare	PCL6 (XL 3.0) PCL 5c PostScript 3 (CPSI 3016) XPS
Sisteme operare	Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix
Fonturi printare	80 PCL Latin; 137 PostScript 3 Emulation Latin
Functii printare	Printare directa PCL, PS, TIFF, XPS, PDF, fisiere PDF criptate si OOXML (DOCX, XLSX, PPTX); mixmedia si mixplex; programare joburi "Easy Set" ; overlay; watermark; protejare copiere; carbon copy print
Specificatii scanner	
Viteza scanare color	Pana la 160 ipm (cu DF-701 optional)
Viteza scanare alb negru	Pana la 160 ipm (cu DF-701 optional)
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB



Imaginea este cu titlu de prezentare

	Scan-to-WebDAV		
	Scan-to-DPWS		
	Scanare TWAIN in retea		
Formate fisier	JPEG; TIFF; PDF; PDF/A 1a si 1b (optional); PDF compact; PDF criptat; PDF indexabil (optional); XPS; XPS compact; PPTX; PPTX indexabil (optional); DOCX/XLSX indexabil (optional)		
Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP		
Functii scanare	Adnotare (text/timp/data) pentru PDF; pana la 400 programe joburi; previzualizare scanare in timp real		
Specificatii fax			
Standard fax	Super G3 (optional)		
Transmisie fax	Analog i-Fax i-Fax color (RFC3949-C) IP-Fax		
Rezolutie fax	Max.: 600 x 600 (ultra-fine) (dpi)		
Compresie fax	MH; MR; MMR; JBIG		
Modem fax	Pana la 33,6 Kbps		
Destinatii fax	2,100 (utilizatori + grupuri)		
Functii fax	Polling; transmisie intarziata; PC-Fax; receptie confidentiala in box; Receptie catre e-mail/FTP/SMB; pana la 400 programe joburi		
Specificatii user box			
Nr. maxim documente care se pot stoca	Pana la 3,000 documente sau 10,000 pagini		
Tipuri de user box	Public Personal (cu parola sau autentificare) Grup (cu autentificare)		
Tipuri de boxuri sistem	Printare securizata Printare PDF criptat Receptie fax Fax polling		
Functionalitati user box	Reprintare; combinare Descarcare Trimitere (e-mail/FTP/SMB si Fax) Copiere din box in box		
Specificatii sistem			
Memorie sistem standard	2,048 (standard) MB		
Hard disk sistem standard	250 (standard) GB		
Interfete standard	10-Base-T/100-Base-T/1.000-Base-T Ethernet; USB 2.0		
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; Apple Talk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP		
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP		
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-163 g/m ² RADF sau Dualscan ADF		
Format hartie	A6-SRA3, formate hartie particularizate; hartie banner max. 1,200 x 297 mm		
Greutate hartie	52-300 g/m ²		
Capacitate alimentare hartie	Standard: 1,150 coli Max.: 6,650 coli		
Casete hartie standard	Caseta 1: 500 coli, A5-A3, 52-256 g/m ² Caseta 2: 500 coli, A5-SRA3, 52-256 g/m ² Alimentare manuala (bypass): 150 coli, A6-SRA3, dimensiuni particularizate, banner, 60-300 g/m ²		
		Caseta 3: 500 coli, A5-A3, 52-256 g/m ² Casetele 3 +4: 2x 500 coli, A5-A3, 52-256 g/m ² Caseta de mare capacitate: 2,500 coli, A4, 52-256 g/m ²	
		Duplex automat	A5-SRA3; 52-256 g/m ²
		Moduli finisare (optional)	Offset; grupare; sortare; capsare; perforare; post inserare; pliere mediana; pliere in forma descriptoare; brosurare
		Capacitate iesire (cu finisher)	Max.: 3,300 coli
		Capacitate iesire (fara finisher)	Max.: 250 coli
		Capsare	50 coli sau 48 coli + 2 coperti (pana la 209 g/m ²)
		Capacitate iesire la capsare	Max. 1,000 coli
		Pliere in forma de scrisoare	Pana la 3 coli
		Capacitate coli pliate in forma de scrisoare	Max.: 30 coli (tava); nelimitat Max.: 20 coli sau 19 coli + 1 coperta (pana la 209 g/m ²)
		Brosura	Max.: 100 coli (tava); nelimitat
		Capacitate iesire brosură	30,000 pagini
		Volum copiere/printare recomandat (lunar)	100,000 pagini
		Volum copiere/printare maxim (lunar)	27000
		Durata viata toner Black	25000
		Durata viata toner CMY	220-240 V / 50/60 Hz
		Consum energie	Mai putin de 1.5 kW (sistem)
		Dimensiuni sistem (LxxH)	615 x 685 x 779 mm (fara ADF si casete suplimentare)
		Greutate sistem	Aprox. 85 kg
		Functii sistem	
			ISO15408 EAL3 (in evaluare), conform IEEE 2600.1, filtrare IP si blocare porturi, criptare comunicare in retea SSL2, SSL3 si TSL 1.0, suport IPsec, suport IEEE 802.1x, autentificare securizata, raport autentificare, printare securizata, suprascriere hard disk (8 tipuri standard), criptare date pe hard disc (AES 128), stergere automata a datelor din memorie, receptionare confidentiala a faxurilor, protectie la copiere (copy guard, parola)
			Pana la 1.000 conturi utilizatori, suport Active Directory (nume utilizator + parola + email + folder smb)
			Definire acces utilizatori
			Autentificare biometrica (scanarea dispunerii venelor in deget) optional
			Autentificare prin card IC-Card (cititor IC-Card) optional
			PageScope Net Care Device Manager
			PageScope Data Administrator
			PageScope Box Operator
			PageScope Direct Print
			Print Status Notifier
			Driver Packaging Utility
			Log Management Utility