

KONICA MINOLTA Bizhub C3850

Viteza A4: 38 ppm color si alb-negru
Formate hartie: A6-A4
Panoul color, tactil, de 7-inch cu operare asemanatoare telefoanelor inteligente face utilizarea placuta si eficienta

Functiile cuprinzatoare de securitate asigura siguranta datelor, a documentelor si a retelei

Performantele eco reduc impactul asupra mediului si economisesc energie si bani

sisteme de operare



Specificatii copiator

Proces copiere	Copiere laser electrostatic, tandem, indirect
Sistem toner	Toner polimerizat Simitri® HD
Viteza copiere/printare A4 alb negru (cpm)	Pana la 38 ppm
Viteza copiere/printare A4 color	Pana la 38 ppm
Viteza duplex A4 alb negru (cpm)	Pana la 38 ppm
Viteza duplex A4 color	Pana la 38 ppm
Prima pagina copiata/printata alb negru (sec)	7,2 sec.
Prima pagina copiata/printata color (sec)	8,1 sec.
Timpul de incalzire (sec)	Aprox. 30 sec.
Rezolutie copiere (dpi)	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1 -999
Format documente originale	Max. A4
Marire-micsorare	25-400% in pasi de 0,1%; zoom automat
Functii copiere	Sortare electronica; lucrare multipla; ajustare (contrast, detaliu, densitate imagine); copie de test; mod intrerupere; mod color; scanare separata; sortare/grupare; combinare; selectie original; copiere acti dentitate; 2-in 1; 4-in-1

Specificatii imprimanta

Rezolutie printare (dpi)	600 x 600 dpi 1200 x 1,200 dpi (viteza redusa)
Limbaje printare	PCL 5e/c, PCL XL Ver. 3.0, PostScript 3 (3016), XPS Ver. 1.0, OpenXPS, PDF 1.7



Imaginea este cu titlu de prezentare

Sisteme operare

Windows XP (32/64), Windows Vista (32/64), Windows 7 (32/64), Windows 8 (32/64), Windows Server 2003 (32/64), Windows Server 2003 R2 (32/64), Windows Server 2008 (32/64), Windows Server 2008 R2, Windows Server 2012, Macintosh OS X Ver.

Fonturi printare

10.2.8 sau mai recent, Linux 80 PCL Latin; 137 PostScript 3

Functii printare

Emulation Latin
Printare directa TIFF, XPS, PDF si OOXML (DOCX, XLSX, PPTX); printare securizata; combinare; n-up; poster; paginare brosură; watermark

Specificatii scanner

Viteza scanare color	Pana la 35 opm
Viteza scanare alb negru (opm)	Pana la 35 opm
Rezolutie scanare (dpi)	Max.: 600 x 600 dpi
Moduri scanare	Scanare-eMail, Scanare-SMB, Scanare-FTP, Scanare-HDD, Scanare-USB, Scanare-WebDAV, Scanare TWAIN in retea
Formate fisier	JPEG; TIFF; PDF; PDF/A (1b); PDF compact; XPS
Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP
Functii scanare	Pana la 400 programe joburi

Specificatii fax

Standard fax	Super G3 (optional)
Transmisie fax	Analog i-Fax
Rezolutie fax (dpi)	Max.: 600 x 600 dpi (ultra-fine)
Compresie fax	MH; MR; MMR; JBIG
Modem fax (Kbps)	Pana la 33,6 Kbps
Destinatii fax	2,100 (utilizatori + grupuri)

Functii fax Transmisie intarziata; PC-Fax; fax forwarding; pana la 400 program dials

Specificatii sistem

Memorie sistem standard 1024 (MB)
 Hard disk sistem standard 320 (GB)
 Interfete standard 10-Base-T/100-Base-TX/1,000-Base-T Ethernet; USB 2.0
 Protocoale de retea TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
 Tipuri frame-uri Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
 Alimentator automat Pana la 50 originale; A5 - A4; 50 - 128 g/m²; alimentator automat de documente duplex
 Format hartie A6 - A4, dimensiuni hartie particularizate
 Greutate hartie (g/m²) 60 - 210 g/m²
 Capacitate alimentare hartie (coli) Standard: 650 coli
 Max.: 1,650 coli
 Casete hartie standard Caseta 1: 550 coli, A6 - A4, 60 - 210 g/m²
 Alimentare manuala (bypass): 100 coli, A6 - A4, dimensiuni particularizate, 60 - 210 g/m²
 Specificatii hartie optional Caseta 3: 500 coli, A4, 60 - 90 g/m²
 Duplex automat A4; 60 - 210 g/m²
 Moduri finisare (optional) Capsare (off-line)
 Capacitate iesire (fara finisher) Max.: 250 coli

Capsare Max.: 20 coli (capsare off-line)
 Volum copiere/printare recomandat (lunar) 6,500 pagini
 Volum copiere/printare maxim (lunar) 120,000 pagini
 Durata viata toner Black 10,000 pagini
 Durata viata toner CMY 10,000 pagini
 Durata viata unitate imagine Black 60,000 pagini
 Durata viata unitate imagine CMY 60,000 pagini
 Consum energie 220 - 240 V/50/60 Hz, mai putin de 1,7 kW
 Dimensiuni sistem (LxHxh) 555 x 584 x 603 mm
 Greutate sistem (kg) Aprox. 47,6 kg

Functii sistem

Securitate ISO 15408 EAL3 (in evaluare); filtrare IP si blocare porturi; comunicare retea SSL2; SSL3 si TSL1.0; suport IPsec; suport IEEE 802.1x; autentificare utilizatori; printare securizata; suprascriere hard disk (8 tipuri standard); criptare date hard disk, protejare copiere (numai printare) Pana la 1,000 conturi utilizatori; suport Active Directory; autentificare card

Contorizare ID optional

Software PageScope Net Care Device
 ManagerPageScope Data
 AdministratorPageScope Direct
 PrintPrint Status NotifierDriver
 Packaging UtilityPageScope Mobile