

KONICA MINOLTA Bizhub C452

Multifunctional rapid cu viteze color/alb-negru de 45/45 ppm

Performante hardware de top 2,048 MB DDR2 RAM, 250 GB SATA-2 hard disc, 1GB Ethernet, PCI-Express bus system

Tehnologii unice cu tonerul polimerizat Simitri HD, controllerul de printare Emperon si tehnologia bEST (bizhub Enhanced Solution Technology)

Printare Eco datorata temperaturii scazute de fixare, tehnologiei Induction fusing si reducerii timpului de incalzire



Imaginea este cu titlu de prezentare

SPECIFICATII COPIATOR

Proces copiere	Copiere laser electrostatic, tandem, indirect
Sistem toner	Toner polimerizat Simitri HD
Viteza copiere/printare A4 alb negru	45 cpm
Viteza copiere/printare A4 color	45 cpm
Viteza copiere/printare A3 alb negru	23 cpm
Viteza copiere/printare A3 color	23 cpm
Viteza duplex A4 alb negru	45 cpm
Viteza duplex A4 color	45 cpm
Prima pagina copiata/printata alb negru	4,8 s
Prima pagina copiata/printata color	6,0 s
Timpu de incalzire	Aprox. 45 sec. (poate varia in functie de mediul ambiant si utilizare)
Rezolutie copiere	600 x 600 dpi
Gradatii	256
Copiere multipla	1 - 9.999
Format documente originale	A5 - A3 25 - 400% in pasi de 0,1%; Marire-micsorare automata
Marire-micsorare	Capitol
Functii copiere	Coperta si inserare pagina Copie de test Test pentru ajustarea printarii Functii pentru arta digitala Memorare setari joburi Mod poster; Repetare imagini Overlay Stampilare Protejare la copiere

Specificatii imprimanta

Rezolutie printare	Echivalent cu 1.800 x 600 dpi
Tip procesor	PowerPC MC7448 @ 1 GHz; 64 BIT
Limbaje printare	PCL 6c (PCL 5c + XL3.0), PostScript 3 (CPSI 3017), XPS
Sisteme operare	Windows 2000, XP, XP64, VISTA 32, VISTA 64 (suport DPWS), Server 2000, Server 2003, Server 2003x64, Server 2008, Server 2008x64 Macintosh 9.x 10.x Unix Linux Citrix
Fonturi printare	80x PCL Latin, 137x PostScript 3
Functii printare	Emulation Latin Printare directa PCL Printare directa PS Printare directa TIFF Printare directa XPS Printare directa fisiere PDF si PDF criptat Mixmedia si mixplex Programare joburi

Specificatii scanner

Viteza scanare color	Pana la 78 opm (300 dpi via DF)
Viteza scanare alb negru	Pana la 78 opm (300 dpi via DF)
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scanare in retea TWAIN Scan-to-eMail (scan-to-Me) Scan-to-FTP Scan-to-SMB (scan-to-Home) Scan-to-Box Scan-to-WebDAV Scan-to-DPWS Scan-to-USB
Formate fisier	JPEG, TIFF, PDF, PDF compact, PDF criptat, XPS, XPS compact
Destinatii scanare	2.100 (simplu + grup); suport LDAP Adnotare (text/ora/data) pentru PDF; pana la 400 programe joburi
Functii scanare	

Specificatii fax

Standard fax	Super G3 (optional) Analogue, i-Fax, Colour i-Fax (RFC3949-C), IP-Fax, SIP-Fax
Transmisie fax	Max.: 600 x 600 dpi (ultra-fin)
Rezolutie fax	MH; MR; MMR; JBIG
Compresie fax	Pana la 33,6 Kbps
Modem fax	2.100 (simple + grup)
Destinatii fax	Polling; Transmisie intarziata; PC-Fax; Receptionare confidentiala in box; Receptionare pe eMail/FTP/SMB; pana la 400 programe joburi
Functii fax	

Specificatii user box

Numar maxim de user box-uri	1.000
Nr. maxim documente care se pot stoca	Pana la 3.000 documente sau 10.000 pagini
Tipuri de user box	Public Personal (cu parola sau autentificare) Grup (cu autentificare)
Tipuri de boxuri sistem	Printare securizata Printare PDF criptat Receptie fax Fax polling
Functionalitati user box	Reprintare; combinare Descarcare Transmisie (email/FTP/SMB and Fax) Copiere din box in box

Specificatii sistem

Memorie sistem standard	2.048 MB
Hard disk sistem standard	250 GB
Interfete standard	10-Base-T/100-Base-T/1.000-Base-T Ethernet; USB 2.0
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-210 gsm A6-A3 full bleed; formate particularizate; hartie tip baner max. 1.200 x 297 mm
Format hartie	64-300 g/mp
Greutate hartie	
Capacitate alimentare hartie	Standard: 3.650 coli Max.: 6.650 coli
Casete hartie standard	Caseta 1: 500 coli; A5-A3+; 64-256 g/mp Caseta 2: 500 coli; A5-A3+; 64-256 g/mp Caseta 3: 1.500 coli; A4; 64-256 g/mp Caseta 4: 1.000 coli; A4; 64-256 g/mp Alimentare manuala (bypass): 150 coli; A6-A3+; formate particularizate; baner 64-300 g/mp Caseta alimentare de mare capacitate (1): 3.000 coli; A4; 64-256 g/mp Caseta alimentare de mare capacitate (2): 2.500 coli; A4-A3+; 64-256 g/mp
Specificatii hartie optional	

Duplex automat	A5-A3+; 64-256 g/mp Offset; grupare; sortare; capsare; perforare; pliere mediana; brosurare
Moduri finisare (optional)	
Capacitate iesire (cu finisher)	Max.: 3.200 coli
Capacitate iesire (fara finisher)	Max.: 250 coli 50 coli sau 48 coli + 2 coli coperta (pana la 209 g/mp)
Capsare	Max. 1.000 coli
Capacitate capsare	15 coli sau 14 coli + 1 coala coperta (pana la 209 g/mp)
Brosura	
Capacitate iesire brosurii	75 coli
Volum copiere/printare recomandat (lunar)	Recomandat.: 65.000; Max.: 150.000
Durata viata toner Black	45000
Durata viata toner CMY	30000
Durata viata unitate imagine Black	285.000/1.140.000 (Drum/Developer)
Durata viata unitate imagine CMY	CMY 120.000
Consum energie	220-240 V / 50/60Hz, mai putin de 2 KW
Dimensiuni sistem (LxIxh)	650 x 879 x 1155
Greutate sistem	Aprox. 221 kg
Functii sistem	
Securitate	ISO 15408 EAL3 (in evaluare) Filtrare IP si blocare porturi comunicare in retea SSL2; SSL3 si TSL1.0 Suport IPsec Suport IEEE 802.1x Autentificare utilizatori Raportare autentificare; Printare securizata Suprascriere hard disk (8 tipuri standard) Criptare date pe hard disk (AES 256) Stergere automata a datelor din memorie Receptionare confidentiala faxuri Criptare date printare ale utilizatorilor Protejare la copiere (copy guard, password) Pana la 1.000 conturi utilizatori
Contorizare	Suport Active Directory (nume utilizator + parola + email + director smb) Functie definire acces utilizatori Autentificare biometrica (scanare dispunere vene in deget) optional Autentificare prin card IC (cititor carduri IC) optional
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility