

KONICA MINOLTA Bizhub C454e

Viteza A4/A3: 45/22 ppm color si alb-negru
Formate hartie: A6-SRA3, formate customizate si banner de pana la 1,2m lungime
Panou de operare tactil, color, de 9 inch cu functionalitate multi-touch
Alimentator dual-scan pentru scanarea documentelor dubla fata la o sigura trecere la viteza de 160 ipm
Finisari modulare si tavi optionale pentru configuratii customizate

Sisteme de operare



Specificatii copiator

	Copiere electrostatica laser, tandem, indirecta
Proces copiere	Toner polimerizat Simitri HD®
Sistem toner	
Viteza copiere/printare A4 alb negru	45 cpm
Viteza copiere/printare A4 color	45 cpm
Viteza copiere/printare A3 alb negru	22 cpm
Viteza copiere/printare A3 color	22 cpm
Viteza duplex A4 alb negru	45 cpm
Viteza duplex A4 color	45 cpm
Prima pagina copiata/printata alb negru	4.6 sec
Prima pagina copiata/printata color	5.5 sec
Timpul de incalzire	Aprox. 25 sec
	* Timpul de incalzire poate varia in functie de mediul ambiant
Rezolutie copiere	600 x 600 dpi
Gradatii	256 gradatii
Copiere multipla	1-9,999
Format documente originale	A5-A3 25-400% in pasi de 0.1%; zoom automat
Marire-micsorare	Capitol; inserare pagina si capitol; copiere de test (print si ecran); ajustare test de print; functii arta digitala; memorare setari joburi; mod poster; repetare imagine; overlay (optional); stampilare; protejare la copiere
Functii copiere	



Imaginea este cu titlu de prezentare

Specificatii imprimanta

Rezolutie printare	1,800 x 600 dpi 1,200 x 1,200 dpi
Procesor	800 MHz
Limbaje printare	PCL6 (XL 3.0); PCL 5c; PostScript 3 (CPSI 3016); XPS
Sisteme operare	Windows XP (32/64) Windows VISTA (32/64) Windows 7 (32/64) Windows 8 (32/64) Windows Server 2003 (32/64) Windows Server 2008 (32/64) Windows Server 2008 R2 (64) Windows Server 2012 (64) Macintosh OS X 10.x Unix, Linux, Citrix
Fonturi printare	80 PCL Latin; 137 PostScript 3 Emulation Latin
Functii printare	Printare directa PCL, PS, TIFF, XPS, PDF, fisiere PDF criptate si OOXML (DOCX, XLSX, PPTX); mixmedia si mixplex; programare joburi "Easy Set"; overlay; watermark; protejare la copiere; carbon copy print
Specificatii scanner	
Viteza scanare color	Pana la 160 ipm
Viteza scanare alb negru	Pana la 160 ipm
Rezolutie scanare	Max.: 600 x 600 dpi
Moduri scanare	Scan-to-eMail (Scan-to-Me) Scan-to-SMB (Scan-to-Home) Scan-to-FTP Scan-to-Box Scan-to-USB Scan-to-WebDAV Scan-to-DPWS Scanare TWAIN in retea

Formate fisier	JPEG; TIFF; PDF; PDF/A 1a si 1b (optional); PDF compact; PDF criptat; PDF indexabil (optional); XPS; XPS compact; PPTX; PPTX indexabil (optional); DOCX/XLSX indexabil (optional)		
Destinatii scanare	2,100 (utilizatori + grupuri); suport LDAP	Duplex automat	Caseta de mare capacitate: 2,500 coli, A4, 52-256 g/m ² Caseta alimentare de mare capacitate (1): 3,000 coli, A4, 52-256 g/m ² Caseta alimentare de mare capacitate (2): 2,500 coli, A4-SRA3, 52-256 g/m ² A5-SRA3; 52-256 g/m ²
Functii scanare	Adnotare (text/timp/data) pentru PDF; pana la 400 programe joburi; previzualizare scanare in timp real	Moduri finisare (optional)	Offset; grupare; sortare; capsare; perforare; pliere mediana; pliere in forma de scrisoare; brosurare
Specificatii fax		Capacitate iesire (cu finisher)	Max.: 3,300 coli
Standard fax	Super G3 (optional)	Capacitate iesire (fara finisher)	Max.: 250 coli
Transmisie fax	Analog i-Fax i-Fax color (RFC3949-C) IP-Fax	Capsare	Max.: 50 coli sau 48 coli + 2 coperti (pana la 209 g/m ²)
Rezolutie fax	Max.: 600 x 600 (ultra-fine) dpi	Capacitate iesire la capsare	Max. 1,000 coli
Compresie fax	MH; MR; MMR; JBIG	Pliere in forma de scrisoare	Pana la 3 coli
Modem fax	Pana la 33.6 Kbps	Capacitate coli pliate in forma de scrisoare	Max.: 30 coli (tava); nelimitat Max.: 20 coli sau 19 coli + 1 coperta (pana la 209 g/m ²)
Destinatii fax	2,100 (utilizatori + grupuri); Polling; transmisie intarziata; PC-Fax; receptie confidentiala in box;	Brosura	Max.: 100 coli (tava); nelimitat
Functii fax	Receptie pe e-mail/FTP/SMB; pana la 400 programe joburi	Capacitate iesire brosururi	Max.: 65,000 pagini
Specificatii user box		Volum copiere/printare recomandat (lunar)	150,000 pagini
Nr. maxim documente care se pot stoca	Pana la 3,000 documente sau 10,000 pagini	Volum copiere/printare maxim (lunar)	27500
Tipuri de user box	Public Personal (cu parola sau autentificare) Grup (cu autentificare)	Durata viata toner Black	26000
Tipuri de boxuri sistem	Printare securizata Printare PDF criptat Receptie fax Fax polling	Durata viata toner CMY	220-240 V / 50/60 Hz
Functionalitati user box	Reprintare; combinaie Descarcare Trimitere (e-mail/FTP/SMB si Fax) Copiere din box in box	Consum energie	Mai putin de 1.5 kW (sistem) 615 x 685 x 921 mm (fara casete)
Specificatii sistem		Dimensiuni sistem (Lxhxh)	suplimentare)
Memorie sistem standard	2,048 (standard) MB	Greutate sistem	Aprox. 101 kg
Hard disk sistem standard	250 (standard) GB	Functii sistem	
Interfete standard	10-Base-T/100-Base-T/1,000-Base-T Ethernet; USB 2.0	Securitate	ISO 15408 EAL3 (in evaluare); conform IEEE 2600.1; filtrare IP si blocare porturi; comunicare in retea SSL2; SSL3 si TSL1.0; suport IPsec; suport IEEE 802.1x; autentificare utilizatori; Raport autentificare; printare securizata; Suprascriere hard disc (8 tipuri standard); Criptare date pe hard disc (AES 128); Stergere automata a datelor din memorie; Receptionare confidentiala a faxurilor; Criptarea datelor printate; protectie la copiere (Copy Guard, parola) optional
Protocoale de retea	TCP/IP (IPv4 / IPv6); IPX/SPX; NetBEUI; AppleTalk (EtherTalk); SMB; LPD; IPP; SNMP; HTTP	Contorizare	Pana la 1,000 conturi de utilizatori; suport Active Directory (nume utilizator + parola + e-mail + folder smb) Definire acces utilizatori Autentificare biometrica (scanarea dispunerii venelor in sange) optional Autentificare prin card acces (cititor card acces) optional
Tipuri frame-uri	Ethernet 802.2; Ethernet 802.3; Ethernet II; Ethernet SNAP	Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility
Alimentator automat documente	Pana la 100 originale; A6-A3; 35-163 g/m ² ADF dualscan		
Format hartie	A6-SRA3, formate hartie particularizate; hartie banner max. 1,200 x 297 mm		
Greutate hartie	52-300 g/m ²		
Capacitate alimentare hartie	Standard: 1,150 coli Max.: 6,650 coli		
Casete hartie standard	Caseta 1: 500 coli, A5-A3, 52-256 g/m ² Caseta 2: 500 coli, A5-SRA3, 52-256 g/m ² Alimentare manuala (bypass): 150 coli, A6-SRA3, dimensiuni particularizate, banner, 60-300 g/m ²		
Specificatii hartie optional	Caseta 3: 500 coli, A5-A3, 52-256 g/m ² Casetele 3 + 4: 2x 500 coli, A5-A3, 52-256 g/m ²		